

Sponsor: Kyunghan Chung Toptec / Lemon 122, Asanvalley-ro, Dunpo-myeon Asan-si, Chungcheongnam-do, 31409 KOREA, REPUBLIC OF

Bacterial Filtration Efficiency (BFE) and Differential Pressure (Delta P) Final Report

Test Article: Study Number: Study Received Date: Testing Facility:	09 Apr 2020 Nelson Laboratories, LLC	
Test Procedure(s): Deviation(s):	6280 S. Redwood Rd. Salt Lake City, UT 84123 U.S.A. Standard Test Protocol (STP) Number: STP0004 Rev 18 None	

Summary: The BFE test is performed to determine the filtration efficiency of test articles by comparing the bacterial control counts upstream of the test article to the bacterial counts downstream. A suspension of Staphylococcus aureus was aerosolized using a nebulizer and delivered to the test article at a constant flow rate and fixed air pressure. The challenge delivery was maintained at 1.7 - 3.0 x 10³ colony forming units (CFU) with a mean particle size (MPS) of 3.0 ± 0.3 µm. The aerosols were drawn through a sixstage, viable particle, Andersen sampler for collection. This test method complies with ASTM F2101-19 and EN 14683:2019, Annex B.

The Delta P test is performed to determine the breathability of test articles by measuring the differential air pressure on either side of the test article using a manometer, at a constant flow rate. The Delta P test complies with EN 14683:2019, Annex C and ASTM F2100-19.

All test method acceptance criteria were met. Testing was performed in compliance with US FDA good manufacturing practice (GMP) regulations 21 CFR Parts 210, 211 and 820.

Test Side:	Smooth Side
BFE Test Area:	~40 cm ²
BFE Flow Rate:	28.3 Liters per minute (L/min)
Delta P Flow Rate:	
	$85 \pm 5\%$ relative humidity (RH) and 21 ± 5 °C for a minimum of 4 hours
Positive Control Average:	1.9 x 10 ³ CFU
Negative Monitor Count:	
MPS:	3.1 µm



1020

Study Completion Date James W. Luskin

Study Director

801-290-7500



ks

US May

These results apply to the samples as received and relate only to the test article listed in this report. Reports may not be reproduced except in their entirety. Subject to NL terms and conditions at www.nelsonlabs.com



Results:

Test Article Number	Percent BFE (%)
1	>99.9 ^a
2	>99.9 ^a
3	>99.9 ^ª
4	>99.9ª
5	>99.9ª

^a There were no detected colonies on any of the Andersen sampler plates for this test article.

Test Article Number	Delta P (mm H ₂ O/cm ²)	Delta P (Pa/cm²)
1	8.8	85.9
2	8.8	86.1
3	8.7	85.5
4	8.8	86.3
5	8.9	87.2

The filtration efficiency percentages were calculated using the following equation:

% BFE =	$\frac{C-T}{T} \times 100$
/0 = 1 =	С

C = Positive control average T = Plate count total recovered downstream of the test article Note: The plate count total is available upon request